https://selldocx.com/products/test-bank-a-guide-to-sql-9e-pratt

Chapter 2: Database Design Fundamentals

True / False

1. The process of determ	ining the particular	r tables and columns that will co	omprise a database is known as database design.
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			21
2. A tabular database is a	a collection of table	es.	
	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			22
3. A relation is a characte	eristic or property	of an entity.	
	a.	True	
	b .	False	
ANSWER:			False
POINTS:			1
REFERENCES:			24
4. Because there is a one sales rep can be associated		or more customers.	omers in the TAL Distributors database, one
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			24
5. In a relational database	e, each entity has i	ts own table.	
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			24
6. A matrix is the associa	ation between entit	ies.	
	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			24

7. In the one-to-many type of relationship, the word many always indicates a large number.

Chapter 2: Database Design Fundamentals True a. b. False ANSWER: False **POINTS:** 1 REFERENCES: 24 8. In a relational database, relationships are implemented by having common columns in two or more tables. True a. False b. ANSWER: True **POINTS:** 25 REFERENCES: 9. Each column in a table of a relational database should have a distinct name. a. True b. False ANSWER: True **POINTS:** 1 REFERENCES: 26 10. In a relation, all values in a column are values of the same attribute. True a. False b. ANSWER: True POINTS: 1 REFERENCES: 26 11. A relation is essentially a three-dimensional table. True a. h. False ANSWER: False **POINTS:** 1 REFERENCES: 26 12. Columns are sometimes called tuples. True False b. ANSWER: False **POINTS:** 1 REFERENCES: 26

13. The concept of functional dependence is trivial to understanding database concepts.

True

False

a.

b.

ANSWER:

False

Chapter 2: Database Design Fundamentals 1 **POINTS:** 27 REFERENCES: 14. In a relation, the order of the rows and columns is immaterial. True a. False b. ANSWER: True **POINTS:** 1 REFERENCES: 26 15. The same column name can appear in two different tables in a relational database. True a. False b. ANSWER: True **POINTS:** 1 REFERENCES: 27 16. The statement "A sales rep's pay class functionally determines his or her pay rate" means that if you know the pay class, you can determine the pay rate. True b. False ANSWER: True POINTS: 1 REFERENCES: 28 17. You can determine functional dependence by viewing sample data. True a. False h. ANSWER: False POINTS: 1 REFERENCES: 29 18. A secondary key is the unique identifier for a table. True a. b. False ANSWER: False **POINTS:** 1

True

False

19. A primary key always comprises a single column.

a. b.

REFERENCES:

ANSWER:

POINTS:

REFERENCES:

30

False

1

30

20. You can indicate a table key for each table in the data		by underlining the column or	collection of columns that comprises the primary
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			31
21. The definition for a prim	nary key really	defines a candidate key as we	ell.
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			31
22. Many organizations and privacy issues.	institutions are	e moving toward using Social	Security numbers as primary keys because of
	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			32
23. If a table contained both candidate keys.	employee num	nbers and Social Security num	nbers, both columns would be referred to as
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			31
24. A programmer interview determine exactly the type of			cuments, and examines organizational policies to
	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			32
25. It is possible for the com	nputer to genera	ate values that are used as the	primary key column.
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			32

26. Normalization is done bef	fore creating t	he database design.	
	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			40
27. An unnormalized relation	is a relation t	hat may contain repeating grou	ups.
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			40
28. When you convert an unn form is usually the concatenate		t two columns.	m, the primary key of the table in first normal
	a.	True	
	b.	False	
ANSWER:			True
POINTS:			1
REFERENCES:			42
29. Qualification is an update	anomaly.		
	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			43 44
30. A table is in third normal the primary key.	form if it is in	second normal form and no n	onkey column is dependent on only a portion of
	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			48
31. A determinant is any colu	mn (or collec	tion of columns) that determine	es another table.
•	a.	True	
	b.	False	
ANSWER:			False
POINTS:			1
REFERENCES:			48

Multiple Choice

32. The proce	ess of de	termining the particular tables and columns that will comprise a databa	se is known	as
	a.	normalization		
	b.	database design		
	c.	qualification		
	d.	relational management		
ANSWER:				b
POINTS:				1
REFERENCI	ES:			21
33. At TAL I	Distribute	ors, there is a relationship between sales reps and customers.		
		a. one-to-one		
	1	b. one-to-two		
		c. one-to-many		
	(d. many-to-many		
ANSWER:				c
POINTS:				1
REFERENCI	ES:			24
34. A(n)	_ is the a	ssociation between entities.		
	a.	qualification		
	b.	functional dependency		
	c.	relationship		
	d.	join		
ANSWER:				c
POINTS:				1
REFERENCE	ES:			24
35. A(n)	_ is a pro	operty of an entity.		
	a.	field		
	b.	. attribute		
	c.	column		
	d.	. All of the above		
ANSWER:			d	
POINTS:			1	
REFERENCI	ES:		24 26	
36. In a relati	ional data	abase each should be unique.		
	a.	row		
	b.	. record		
	c.	tuple		
	d.	. All of the above		
ANSWER:			d	
POINTS:			1	
REFERENCE	ES:		24 26	

			orthand representation to le are listed within a set	show the structure of a relation	al database: After the name
of the table, at	a.		e brackets		
	b.	•	theses		
	c.	-	slashes		
	d.		braces		
ANSWER:		,			ь
POINTS:					1
REFERENCE	S:				26
38. A field is a	another term	for a(n) _	·		
		a.	tuple		
		b.	row		
		c.	column		
		d.	entity		
ANSWER:					c
POINTS:					1
REFERENCE	S:				26
39. A record is	s another ter	m for a(n)			
		a.	row		
		b.	field		
		c.	attribute		
		d.	property		
ANSWER:					a
POINTS:					1
REFERENCE	S:				26
40. Which of t	the following		s used to qualify column	names?	
	a.	-	od (.)		
	b.		ma (,)		
	c.		slash (/)		
	d.	pou	nd sign (#)		
ANSWER:					a
POINTS:					1
REFERENCE	S:				27
41. Which of t		g is the pri	nary key of the ORDER_	LINE (ORDER_NUM, ITEM_	NUM, NUM_ORDERED,
a.	· ·	R_NUM			
b.					
c.	_	ED PRIC	3		
d.		_	d ITEM NUM		
ANSWER:		_	_		d
POINTS:					1

REFERENCES:			31	1
42. A relation is in	if it do	es not contain any repeating groups.		
a.	first nor	nal form		
b.	second n	ormal form		
c.	third nor	mal form		
d.	Boyce-C	odd normal form		
ANSWER:			a	
POINTS:			1	
REFERENCES:			40)
43 is the form	mal term for a.	combining two or more columns to form a primary Qualification	y key.	
	b.	Joining		
	c.	Normalization		
	d.	Concatenation		
ANSWER:			d	
POINTS:			1	
REFERENCES:			42	
44 :- 41 4	.1:	4-		
44 is the dup				
		epeating group edundancy		
		eplication		
		-		
ANCHIED	d. A	nomaly	1.	
ANSWER:			b	
POINTS:			1	,
REFERENCES:			43	3
45 is one of	the categorie	of update anomalies.		
		onal dependence		
b.	Function	onal splitting		
c.	Incons	stent data		
d.	Qualif	cation		
ANSWER:			c	
POINTS:			1	
REFERENCES:			43 44	
46 A column	n is a column	that is not part of the primary key.		
40. 71 Column	a.	determinant		
	b.	candidate		
	c.	functional		
	d.	nonkey		
ANSWER:			d	
POINTS:			1	

REFEI	RENCES:			44
47.	can occui	when tl	here is a column in a table that is dependent on only a portion of the primary	key.
		a.	Qualification	
		b.	Update anomalies	
		c.	Function splitting	
		d.	Determination	
ANSW	ER:		b	
POINT	TS:		1	
REFEI	RENCES:		43 44	
48. An	y column (o	or collect	tion of columns) that determines another column is called a(n)	
	`	a.	nonkey column	
		b.	primary key	
		c.	dependency	
		d.	determinant	
ANSW	ER:			d
POINT	TS:			1
REFEI	RENCES:			48
49. In 1	this text, Bo	yce-Cod	ld normal form is the same as	
	a		unnormalized	
	b).	first normal form	
	c		second normal form	
	d	l .	third normal form	
ANSW	ER:			d
POINT	TS:			1
REFEI	RENCES:			48
50. In a	an entity-rel	ationshi	p (E-R) diagram, are used to represent an entity.	
		a	. rectangles	
		b	ovals	
		c	. circles	
		d	. diamonds	
ANSW	ER:			a
POINT	TS:			1
REFEI	RENCES:			51
51. In a	an entity-rel	ationshi	p (E-R) diagram, one-to-many relationships between entities are drawn as	
	•	a.	ovals	
		b.	equal signs	
		c.	lines	
		d.	circles	
ANSW	ER:			c
POINT				1

REFERENCES: 51

Completion			
52. A(n)	is a person, place, thing, or event for	which you want to s	tore and process data.
ANSWER:			entity
POINTS:			1
REFERENCES:			23
53. A(n)	is the association between entities.		
ANSWER:		relationship	
POINTS:		1	
REFERENCES:		24	
54. A relationship is an as	ssociation between		
ANSWER:		entitie	es
POINTS:		1	
REFERENCES:		24	
	ld be as simple as possible; you should restrict (called a(n) group) ir		
ANSWER:	S-1 ap)	repeating	
POINTS:		1	
REFERENCES:		25	
56. A relational database	is a collection of		
ANSWER:			
		relations tables	
POINTS:		1	
REFERENCES:		26	
57. In a relation, the	of the rows and columns i	s immaterial.	
ANSWER:			order
POINTS:			1
REFERENCES:			26
58. A(n)	is another name for a record or a row.		
ANSWER:			tuple
POINTS:			1
REFERENCES:			26
59. When you combine a	column name with a table name, you are said t		the column name.
ANSWER:		quali	fy
POINTS:		1	
REFERENCES:		27	

60. When you write a column in the format C column name.	CUSTOMER.REP_NUM, you say that you	the
ANSWER:	qualify	
POINTS:	1	
REFERENCES:	27	
61. In a relational database, column B is A determines a single value for B.	on another column A, if at any poin	nt in time a value fo
ANSWER:	functionally dependent	
POINTS:	1	
REFERENCES:	28	
62. If B is functionally dependent on A, you a	lso can say that A functionally	В.
ANSWER:	determines	_
POINTS:	1	
REFERENCES:	28	
63. The key of a tab	le (relation) is the column or collection of columns that	uniquely identifies
given row in that table.		
ANSWER:	primary	
POINTS:	1	
REFERENCES:	30	
	normal form if it does not contain any repeating groups.	
ANSWER:	fi	rst
		NF
POINTS:	1	
REFERENCES:	40)
65. The four categories of update anomalies a	re additions, deletions, inconsistent data, and	·
ANSWER:	updates	
POINTS:	1	
REFERENCES:	43 44	
66. A(n) column is a	a column that is not part of the primary key.	
ANSWER:	nonkey	
POINTS:	1	
REFERENCES:	44	
67. If the primary key of a table contains only normal form.	a single column, the table is automatically in	
ANSWER:	second	
POINTS:	1	
REFERENCES:	44	
68. is an	nother name given to third normal form in this text.	

ANSWER:			
	BCNF (Boyce-C	odd normal form)	
	Boyce-Codd norm	al form (BCNF)	
	Boyce-Codd		
	BCNF		
POINTS:	1		
REFERENCES:	48		
69. In one style of entity-rel of a relationship.	lationship (E-R) diagrams, a cr	row's foot is used to represent the	side
ANSWER:		many	
POINTS:		1	
REFERENCES:		52	
70. In one style of entity-rela relationship.	lationship (E-R) diagrams, the	letter n is used to represent the	side of
ANSWER:		many	
POINTS:		1	
REFERENCES:		52	
71. In one style of entity-rel	lationship (E-R) diagrams, diag	monds are used to describe	
ANSWER:		relationships	
POINTS:		1	
REFERENCES:		52	

Essay

72. How does a DBMS that follows the relational model handle entities, attributes of entities, and relationships between entities?

ANSWER:

Entities and attributes are fairly simple. Each entity has its own table. The attributes of an entity become the columns in the table. In a relational model database a one-to-many relationship is represented by using common columns in two or more tables. More formally, a relation is essentially a two-dimensional table. Each column in a table should have a unique name, and entries within each column should all "match" this column name. Also, each row (also called a record or a tuple in some programs) should be unique. After all, if two rows in a table contain identical data, the second row doesn't provide any information that you don't already have. In addition, for maximum flexibility in manipulating data, the order in which columns and rows appear in a table should be immaterial. Finally, a table's design should be as simple as possible; you should restrict each position in a table to a single entry by not allowing multiple entries (called a repeating group) in an individual location in the table.

POINTS: 1
REFERENCES: 23|26

73. Define a relation.

ANSWER:

A relation is a two-dimensional table in which:

- 1. The entries in the table are single-valued; that is, each location in the table contains a single entry.
- 2. Each column has a distinct name (technically called the attribute name).
- 3. All values in a column are values of the same attribute (that is, all entries must match the column name).

- 4. The order of columns is immaterial.
- 5. Each row is distinct.
- 6. The order of rows is immaterial.

POINTS: 1
REFERENCES: 26

74. What is the precise definition of a primary key?

ANSWER: Column A (or a collection of columns) is the primary key for a table if:

Property 1: All columns in the table are functionally dependent on A.

Property 2: No subcollection of the columns in A (assuming A is a collection of columns and not just

a single column) also has property 1.

POINTS: 1
REFERENCES: 30

75. What are the six steps necessary to design a database for a set of requirements?

ANSWER:

- 1. Read the requirements, identify the entities (objects) involved, and name the entities.
- 2. Identify the unique identifiers for the entities identified in step 1.
- 3. Identify the attributes for all the entities.
- 4. Identify the functional dependencies that exist among the attributes.
- 5. Use the functional dependencies to identify the tables by placing each attribute with the attribute or minimum combination of attributes on which it is functionally dependent.
- 6. Identify any relationships between tables.

POINTS: 1

REFERENCES: 32|33